

ALPHA 215 Specifications

Size	215
Case Dimensions (With Power Supply)	28.9" Length x 4.5" Height x 2.1" Depth (73.4 cm L x 11.4 cm H x 5.3 cm D)
Weight	6.25 lbs. Including display, power supply and IR keyboard
Display Dimensions	27" Length x 2.1 " Height (68.6 cm L x 5.3 cm H)
Display Array	90 x 7 pixels
Characters Displayed	15 Minimum/Typical 27 Condensed Rotate
Display Memory	215R 7,000 characters - optional upgrade 31,000 215C 6,000 characters - optional upgrade 30,000

Pixel Size (Diameter):	.2" (.05 cm)	Serial Computer Interface:	RS232 and RS485 (multi-drop networking for up to 255 displays)
Center-to-Center Pixel Spacing (Pitch):	.3" (0.8 cm)	Keyboard:	Handheld, IR remote operated.
Character Array	5 x 7	Software Packages:	AlphaNET <i>plus</i> Windows™
Character Size	2." (5.1 cm)	Power Cord Length:	US: 10' ft. (3m)
Character Set:	International Character Set, Block (sans serif), decorative (serif), upper/lower case, slim, wide,	Power:	40W in-line transformer, 120VAC ± 10%, UL listed and CSA Certified Power Supply
Memory Retention:	One month typical	Case Material:	ABS high impact plastic
Message Capacity:	81 different messages can be stored and displayed	Limited Warranty:	One-year parts and labor, USA factory servicing
Message Operating Modes:	-26 consisting of: Automode™, Hold, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Interlock, Spray-On, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, Condensed Rotate -Continuous message entry with automatic centering in any mode -User programmable logos and graphics. -Five hold speeds	Built-in Animations:	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Running Animal, Moving Auto, Welcome (script) and Thank You (script)
Pixel (LED) Color:	(215C) 8 bright colors and 3 rainbow effects (215R) Red only	Operating Temperature:	32F° to 120F° ; 0° C- 49° C
Real-Time Clock:	Day and time, 12 or 24 hour format, maintains accurate time without power for up to 30 days typical	Humidity Range:	0% to 95% non-condensing
		Mounting:	Hardware to accommodate ceiling or wall mounting.

Salecaster® Displays Corporation Since 1950!

www.salecaster.com

800 346-4474