

ALPHA™ 4000 Specifications

Sizes	4080C	4120C/R	4160C/R	4200C/R	4240C/R
Case Dimensions Power supply 5.5"D	28.2" L x 7.7" H	40.1" L x 7.7" H	52.1" L x 7.7" H	64.1" L x 7.7" H	76.1" L x 7.7" H
Weight	13 lbs. (5.8 kg.)	18.5 lbs. (8.4 kg.)	24.5 lbs. (11.2 kg.)	31 lbs. (14.1.8 kg.)	37.5 lbs. (17 kg.)
Display Dimensions	24" L x 4.8" H 60.9cm x 12.2cm	36" L x 4.8" H 91.4cm x 12.2cm	48" L x 4.8" H 121.9cm x 12.2cm	60" L x 4.8" H 152.4cm x 12.2cm	72" L x 4.8" H 182.8cm x 12.2cm
Display Array	80 x 16 pixels	120 x 16 pixels	160 x 16 pixels	200 x 16 pixels	240 x 16 pixels
Character Display	Min / Typical / Max	Min / Typical / Max	Min / Typical / Max	Min / Typical / Max	Min / Typical / Max
1 line of 4.8"	6 8 10	10 12 15	14 16 20	18 20 25	20 24 30
2 lines of 2.1"	26 26 40	40 40 60	52 52 80	66 66 100	80 80 120
Display Memory	28,000 characters	28,000 characters	28,000 characters	28,000 characters	28,000 characters

Pixel Size (Diameter):	.02" (0.5 cm)	Serial Computer Interface:	RS232 and RS485 (multi-drop networking for up to 255 displays <i>Options</i> - Ethernet LAN interface - Communications Protocol
Pixel (LED) Color:	Each dot can be red, green or amber and three rainbow effects (4120R, 4160R 4200R are red only)	Keyboard:	Handheld, IR remote operated.
Center-to-Center Pixel Spacing (Pitch):	.3" (0.8 cm)	Software Packages:	AlphaNET <i>plus</i> Windows™
Character Size (One-line) (Two-line)	4.8" (12.2 cm) 2.1" (4.3 cm)	Power Cord Length:	10' (3 m)
Character Set:	International Character Set, Block (sans serif), decorative (serif), upper/lower case, slim, wide,	Power:	120VAC +/- 10% - 180 watts max for all models except 4120R, 4160R and 4200R (120 watts) Optional 230VAC
Memory Retention:	One month typical	Case Material:	Extruded aluminum
Message Capacity:	81 different messages can be stored and displayed	Limited Warranty:	One-year parts and labor, USA factory servicing
Message Operating Modes:	-25 consisting of: Automode, Hold, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Interlock, Spray-On, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, Condensed Rotate -Continuous message entry with automatic centering in any mode -User programmable logos and graphics -Five hold speeds	Agency Approvals:	120 VAC Model: Listed to ANSI/UL 1950-2 nd Edition (US) and CAN/CSA 22.2 No. 950-M89 (Canada) 230 VAC Model: Complies with EN 60950: 1992 (Europe) and AS/NZS 3260-1993 (Australia/New Zealand)
Built-in Animations:	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Running Animal, Moving Auto, Welcome (script) and Thank You (script)	Operating Temperature: Humidity Range:	32F° to 120F° ; 0° C- 49° C 0% to 95% non-condensing
Real-Time Clock:	Day and time, 12 or 24 hour format, maintains accurate time without power for up to 30 days typical	Mounting:	Hardware to accommodate ceiling, wall or counter mounting

Salecaster® Displays Corporation Since 1950!

www.salecaster.com

800 346-4474