



BPC-49940/2-4/IRR

SPECIFICATIONS

- TYPE:**----- DIGITAL
DISPLAY:----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
CHARACTER HEIGHT:----- 4" (101.6 mm) 9 THOUSAND 9 HUNDRED AND 99
VISIBILITY:----- 250 Ft. (76.2 METERS)
POWER REQUIREMENTS:-- 120V 50Hz 1400 ma AT 9VAC (**TRANSFORMER SUPPLIED**)
FRAME:----- 8.25" x 15.25" x 1.375" ALUMINUM (**BLACK ANODIZED**)
WEIGHT:----- 4.5 lbs.
OPERATING TEMP.:----- -17° TO 182°F
HUMIDITY:----- 0% TO 95% NON-CONDENSING
OPERATING MODE ----- **COUNT UP OR DOWN BY 1. FAST SET UP OR DOWN BY HOLDING KEY DOWN FOR OVER 3 SEC. HOLDING BOTH KEYS DOWN FOR 3 SEC RESETS TO ZERO.**

(F.FWD) KEY IS UP, (REW) KEY IS DOWN, (STOP) KEY IS ZERO AND THE (STOP) KEY HELD FOR 5 SEC SELECTS 2 OR 4 DIGITS

